

Aliance

QUALITY IS OUR STRENGTH



AllianceGator.com

SUPER SAND BOND

POLYMERIC SAND • SABLE POLYMERIQUE
FOR JOINTS UP TO 1" • POUR JOINTS DE PAVÉS DE BÉTON JUSQU'À 2,5 CM
FOR RESIDENTIAL USE • POUR USAGE RESIDENTIEL

NOUVELLE FORMULE
SANS VOILE
LANCHÂTRE

SETTING TIME **1HR**


SETS ABOVE **0°C**

15 YEAR
LIMITED WARRANTY

ADVANCED
HAZE FREE
TECHNOLOGY

5 MORE REASONS TO CHOOSE SUPERSAND



	GATOR SUPERSAND	COMPETITION
Sets at above freezing temperature (0°C)	Yes	No
Can be applied even if it rains 1 hour after installation	Yes	No
4 Exclusive and unique colors 	Yes	No
Vehicular traffic 24 hours after Installation	Yes	No
Extremely competitive pricing	Yes	No
Use blower after sweeping and watering	Yes	Yes

SIMPLY THE BEST!
CLEANEST • STRONGEST • MOST DURABLE

Aliance

QUALITY IS OUR STRENGTH



Residential Applications
Patios, walkways, driveways



Residential & Commercial Applications
Overlay and Non-Overlay Usage
XTRA BONDING • XTRA DURABLE • XTRA STRENGTH

QUICK & EASY INSTALLATION STEPS

1. **Spread & Sweep** Polymeric Sand into joints.



2. **Vibrate** the Polymeric Sand into the paver joints (repeat steps 1 & 2).



3. **Sweep off** excess Polymeric Sand.



4. **Blow off** any remaining Polymeric Sand on paver pores and crevices.



5. **Activate** Polymeric Sand by showering 100 sq.ft. Immediately **shower and rinse** simultaneously 100 sq.ft for **15 seconds**. Repeat.



6. **Blow off** any excess water remaining on the paver pores and crevices.

